



AX7 SpotLite™

Data sheet

Optical

Colours
RGBW

Total LED power
60W

Luminous Flux
1675Lm

Emittance (@2m)
6250Lx

Strobe
0-25Hz

Beam Angle
13°

Pixels
1

Electrical

Battery
Samsung Lithium-ion

Battery Lifetime
70% after 300 cycles

LED Lifetime
50.000 Hours

Charging time (nominal)
7 Hours

Input Voltage
90-264V 47-63Hz

Input Current
1.8A/115VAC ~ 1.0A/230VAC

Inrush Current
Cold start 60A/230VAC

Control

Wireless Modules
865-870MHz
902-928MHz
2.4GHz

Range
300m | 330 Yards

DMX
Supports CRMx and W-DMX

Construction

Housing
Aluminium

IP Rating
IP65

Relative humidity
0-100%







Operating Temperature
0-40 °C
32-104 °F

Weight
6.1kg
13.4Lbs

Dimensions
279 x 296 x 253 (mm)
10.9 x 11.6 x 9.9 (inches)

Environment
Indoor | Outdoor

Accessories

-  Powercon True1 cord
AX10-CHR (Included)
-  32° Flood diffusor
AX10-DDSK (Included)
-  13°x 46° Wallwash diffusor
AX10-WWDSK (Included)
-  13°x 46° Rotatable diffusor
AX10-ROTAD
-  Charging case
AX10-CHRCSE
-  Super bolt
AX10-BLT

