

DMX PROFILES FOR

PLUTOFRESNEL (AF80) AND LEOFRESNEL (AF250)

This document has two tables of contents. The first one is based on the pixel count and whether strobe or fan is turned on or off.

The second one is a numeric index where you can locate a DMX table by its number quickly.

Profiles in logical order

Pixel=1 Strobe=Off	5
1: RGB (PIXEL = 1; STROBE = OFF).....	5
2: RGBW (PIXEL = 1; STROBE = OFF).....	5
3: RGBAW (PIXEL = 1; STROBE = OFF).....	5
4: DIM RGB (PIXEL = 1; STROBE = OFF).....	5
5: DIM RGBW (PIXEL = 1; STROBE = OFF).....	5
6: DIM RGBAW (PIXEL = 1; STROBE = OFF).....	5
7: RGB CCT DIM IND (PIXEL = 1; STROBE = OFF).....	6
89: D CCT GM CRO RGB (PIXEL = 1; STROBE = OFF).....	6
90: D CCT GM HUE SAT (PIXEL = 1; STROBE = OFF).....	6
91: D16 CCT GM C RGB (PIXEL = 1; STROBE = OFF).....	7
92: D16 CCT GM H SAT (PIXEL = 1; STROBE = OFF).....	7
93: D16 X Y (PIXEL = 1; STROBE = OFF).....	7
168: D CCT GM CRO XY (PIXEL = 1; STROBE = OFF).....	7
169: D16 CCT GM C XY (PIXEL = 1; STROBE = OFF).....	8
Pixel=1 Strobe=On	9
8: RGBS (PIXEL = 1; STROBE = ON).....	9
9: RGBWS (PIXEL = 1; STROBE = ON).....	9
10: RGBAWS (PIXEL = 1; STROBE = ON)	9
11: DIM RGBS (PIXEL = 1; STROBE = ON).....	9
12: DIM RGBWS (PIXEL = 1; STROBE = ON).....	10
13: DIM RGBAWS (PIXEL = 1; STROBE = ON).....	10
14: RGB CCT DIM IND S (PIXEL = 1; STROBE = ON).....	10
94: D CCT GM CRO RGB S (PIXEL = 1; STROBE = ON)	11
95: D CCT GM HUE SAT S (PIXEL = 1; STROBE = ON)	11
96: D16 CCT GM H SAT S (PIXEL = 1; STROBE = ON)	11
97: D16 X Y S (PIXEL = 1; STROBE = ON).....	12
137: D16 CCT GM C RGB S (PIXEL = 1; STROBE = ON)	12
170: D CCT GM CRO XY S (PIXEL = 1; STROBE = ON).....	12
171: D16 CCT GM C XY S (PIXEL = 1; STROBE = ON)	13



Pixel=1 Strobe=Off Fan=On	14
144: RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	14
145: RGBW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	14
146: RGBAW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	14
147: DIM RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	14
148: DIM RGBW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	15
149: DIM RGBAW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	15
150: RGB CCT DIM IND FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	15
151: D CCT GM CRO RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	16
152: D CCT GM HUE SAT FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	16
153: D16 CCT GM C RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	17
154: D16 CCT GM H SAT FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	17
155: D16 X Y FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	17
172: D CCT GM CRO XY FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	18
173: D16 CCT GM CRO XY FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	18
Pixel=1 Strobe=On Fan=On.....	19
156: RGBS FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	19
157: RGBWS FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	19
158: RGBAWS FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	19
159: DIM RGBS FAN (PIXEL = 1; STROBE = ON; FAN = ON)	20
160: DIM RGBWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)	20
161: DIM RGBAWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)	20
162: RGB CCT DIM IND S FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	21
163: D CCT GM CRO RGB S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	21
164: D CCT GM HUE SAT S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	22
165: D16 CCT GM C RGB S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	22
166: D16 CCT GM H SAT S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	23
167: D16 X Y S FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	23
174: D CCT GM CRO XY S FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	24
175: D16 CCT GM CRO XY S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	24
Effect Modes Fan=Off	25
15: EFFECT MODE FIX	25
16: EFFECT MODE RGB	29
Effect Modes Fan=On	30
176: EFFECT MODE FIX FAN (FAN = ON).....	30
177: EFFECT MODE RGB FAN (FAN = ON).....	34
Index Colors	35

Profiles in numerical order

1: RGB (PIXEL = 1; STROBE = OFF).....	5
2: RGBW (PIXEL = 1; STROBE = OFF).....	5
3: RGBAW (PIXEL = 1; STROBE = OFF).....	5
4: DIM RGB (PIXEL = 1; STROBE = OFF).....	5
5: DIM RGBW (PIXEL = 1; STROBE = OFF).....	5
6: DIM RGBAW (PIXEL = 1; STROBE = OFF).....	5
7: RGB CCT DIM IND (PIXEL = 1; STROBE = OFF).....	6
8: RGBS (PIXEL = 1; STROBE = ON).....	9
9: RGBWS (PIXEL = 1; STROBE = ON).....	9
10: RGBAWS (PIXEL = 1; STROBE = ON)	9
11: DIM RGBS (PIXEL = 1; STROBE = ON).....	9
12: DIM RGBWS (PIXEL = 1; STROBE = ON).....	10
13: DIM RGBAWS (PIXEL = 1; STROBE = ON).....	10
14: RGB CCT DIM IND S (PIXEL = 1; STROBE = ON).....	10
15: EFFECT MODE FIX	25
16: EFFECT MODE RGB	29
89: D CCT GM CRO RGB (PIXEL = 1; STROBE = OFF).....	6
90: D CCT GM HUE SAT (PIXEL = 1; STROBE = OFF).....	6
91: D16 CCT GM C RGB (PIXEL = 1; STROBE = OFF).....	7
92: D16 CCT GM H SAT (PIXEL = 1; STROBE = OFF)	7
93: D16 X Y (PIXEL = 1; STROBE = OFF).....	7
94: D CCT GM CRO RGB S (PIXEL = 1; STROBE = ON)	11
95: D CCT GM HUE SAT S (PIXEL = 1; STROBE = ON)	11
96: D16 CCT GM H SAT S (PIXEL = 1; STROBE = ON)	11
97: D16 X Y S (PIXEL = 1; STROBE = ON).....	12
137: D16 CCT GM C RGB S (PIXEL = 1; STROBE = ON)	12
144: RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	14
145: RGBW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	14
146: RGBAW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	14
147: DIM RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	14
148: DIM RGBW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	15
149: DIM RGBAW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	15
150: RGB CCT DIM IND FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	15
151: D CCT GM CRO RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	16
152: D CCT GM HUE SAT FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	16
153: D16 CCT GM C RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	17



154: D16 CCT GM H SAT FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	17
155: D16 X Y FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	17
156: RGBS FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	19
157: RGBWS FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	19
158: RGBAWS FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	19
159: DIM RGBS FAN (PIXEL = 1; STROBE = ON; FAN = ON)	20
160: DIM RGBWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)	20
161: DIM RGBAWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)	20
162: RGB CCT DIM IND S FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	21
163: D CCT GM CRO RGB S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	21
164: D CCT GM HUE SAT S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	22
165: D16 CCT GM C RGB S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	22
166: D16 CCT GM H SAT S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	23
167: D16 X Y S FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	23
168: D CCT GM CRO XY (PIXEL = 1; STROBE = OFF).....	7
169: D16 CCT GM C XY (PIXEL = 1; STROBE = OFF)	8
170: D CCT GM CRO XY S (PIXEL = 1; STROBE = ON).....	12
171: D16 CCT GM C XY S (PIXEL = 1; STROBE = ON)	13
172: D CCT GM CRO XY FAN (PIXEL = 1; STROBE = OFF; FAN = ON).....	18
173: D16 CCT GM CRO XY FAN (PIXEL = 1; STROBE = OFF; FAN = ON)	18
174: D CCT GM CRO XY S FAN (PIXEL = 1; STROBE = ON; FAN = ON).....	24
175: D16 CCT GM CRO XY S FAN (PIXEL = 1; STROBE = ON; FAN = ON)	24
176: EFFECT MODE FIX FAN (FAN = ON).....	30
177: EFFECT MODE RGB FAN (FAN = ON).....	34
Index Colors	35

Pixel=1 Strobe=Off

1: RGB (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)

2: RGBW (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)

3: RGBA (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Amber (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)

4: DIM RGB (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)

5: DIM RGBW (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)

6: DIM RGBA (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Amber (0% → 100%)
6	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)

7: RGB CCT DIM IND (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 4 4 - 255	0 - 1.5 1.6-100	Color Temperature (CCT) No effect Display color temperature Formular: $CCT = 2000 + 20 \cdot DMX\text{-Value}$ Example: 50 → 3000K 100 → 4000K 150 → 5000K <small>*CCT overwrites the RGB setting</small>
5	0..255	0 - 100	Dimmer (closed → open)
6	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors No effect Display Index Colors (full list at the end of this document) <small>*Index Colors overwrites both, RGB and CCT</small>

89: D CCT GM CRO RGB (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: $CCT = 1750 + 32 \cdot DMX\text{-Value}$ Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: $G/M = 100\% * (DMX\text{-Value}/128 - 1)$
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5	0 - 255	0 - 100	Intensity Red (0% → 100%)
6	0 - 255	0 - 100	Intensity Green (0% → 100%)
7	0 - 255	0 - 100	Intensity Blue (0% → 100%)

90: D CCT GM HUE SAT (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: $CCT = 1750 + 32 \cdot DMX\text{-Value}$ Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: $G/M = 100\% * (DMX\text{-Value}/128 - 1)$
4	0 - 255	0 - 100	Hue (0° → 360°)
5	0 - 255	0 - 100	Saturation (0% → 100%)

91: D16 CCT GM C RGB (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
6	0 - 255	0 - 100	Intensity Red (0% → 100%)
7	0 - 255	0 - 100	Intensity Green (0% → 100%)
8	0 - 255	0 - 100	Intensity Blue (0% → 100%)

92: D16 CCT GM H SAT (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5 HI			Hue
6 LO	0 - 65535	0 - 100	0° → 360°
7	0 - 255	0 - 100	Saturation (0% → 100%)

93: D16 X Y (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer
2 LO	0 - 65535	0 - 100	closed → open
3 HI			X
4 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
5 HI			Y
6 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535

168: D CCT GM CRO XY (PIXEL = 1; STROBE = OFF)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5 HI			X
6 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
7 HI			Y
8 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535

**169: D16 CCT GM C XY (PIXEL = 1; STROBE = OFF)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
6 HI			X
7 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
8 HI			Y
9 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535



Pixel=1 Strobe=On

8: RGBS (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

9: RGBWS (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
5	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

10: RGBAWS (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Amber (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
6	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

11: DIM RGBS (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

**12: DIM RGBWS (PIXEL = 1; STROBE = ON)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
6	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

13: DIM RGBAWS (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Amber (0% → 100%)
6	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
7	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

14: RGB CCT DIM IND S (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 4 4 - 255	0 - 1.5 1.6 - 100	Color Temperature (CCT) No effect Display color temperature Formula: CCT = 2000 + 20*DMX-Value Example: 50 → 3000K 100 → 4000K 150 → 5000K <i>*CCT overwrites the RGB setting</i>
5	0..255	0 - 100	Dimmer (closed → open)
6	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors No effect Display Index Colors (full list at the end of this document) <i>*Index Colors overwrites both, RGB and CCT</i>
7	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)



DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

94: D CCT GM CRO RGB S (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32*DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5	0 - 255	0 - 100	Intensity Red (0% → 100%)
6	0 - 255	0 - 100	Intensity Green (0% → 100%)
7	0 - 255	0 - 100	Intensity Blue (0% → 100%)
8	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

95: D CCT GM HUE SAT S (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32*DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Hue (0° → 360°)
5	0 - 255	0 - 100	Saturation (0% → 100%)
6	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

96: D16 CCT GM H SAT S (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			
2 LO	0 - 65535	0 - 100	Dimmer closed → open
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32*DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5 HI			
6 LO	0 - 65535	0 - 100	Hue 0° → 360°
7	0 - 255	0 - 100	Saturation (0% → 100%)
8	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)



DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

97: D16 X Y S (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3 HI			X
4 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
5 HI			Y
6 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535
7	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

137: D16 CCT GM C RGB S (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
6	0 - 255	0 - 100	Intensity Red (0% → 100%)
7	0 - 255	0 - 100	Intensity Green (0% → 100%)
8	0 - 255	0 - 100	Intensity Blue (0% → 100%)
9	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

170: D CCT GM CRO XY S (PIXEL = 1; STROBE = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5 HI			X
6 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
7 HI			Y
8 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535
9	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

**171: D16 CCT GM C XY S (PIXEL = 1; STROBE = ON)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
6 HI			X
7 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
8 HI			Y
9 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535
10	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2,0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)

Pixel=1 Strobe=Off Fan=On

144: RGB FAN(PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71-100	28 - 39	Fan Fast Speed
	101-128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

145: RGBW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
5	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71-100	28 - 39	Fan Fast Speed
	101-128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

146: RGBAW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Amber (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
6	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71-100	28 - 39	Fan Fast Speed
	101-128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

147: DIM RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71-100	28 - 39	Fan Fast Speed
	101-128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

148: DIM RGBW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
6	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

149: DIM RGBAW FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Amber (0% → 100%)
6	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
7	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

150: RGB CCT DIM IND FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 4 4 - 255	0 - 1.5 1.6-100	Color Temperature (CCT) No effect Display color temperature Formular: CCT = 2000 + 20*DMX-Value Example: 50 → 3000K 100 → 4000K 150 → 5000K <i>*CCT overwrites the RGB setting</i>
5	0..255	0 - 100	Dimmer (closed → open)
6	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors No effect Display Index Colors (full list at the end of this document) <i>*Index Colors overwrites both, RGB and CCT</i>
7	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

151: D CCT GM CRO RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5	0 - 255	0 - 100	Intensity Red (0% → 100%)
6	0 - 255	0 - 100	Intensity Green (0% → 100%)
7	0 - 255	0 - 100	Intensity Blue (0% → 100%)
8	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

152: D CCT GM HUE SAT FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Hue (0° → 360°)
5	0 - 255	0 - 100	Saturation (0% → 100%)
6	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)**153: D16 CCT GM C RGB FAN (PIXEL = 1; STROBE = OFF; FAN = ON)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
6	0 - 255	0 - 100	Intensity Red (0% → 100%)
7	0 - 255	0 - 100	Intensity Green (0% → 100%)
8	0 - 255	0 - 100	Intensity Blue (0% → 100%)
9	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

154: D16 CCT GM H SAT FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5 HI			Hue 0° → 360°
6 LO	0 - 65535	0 - 100	Saturation (0% → 100%)
7	0 - 255	0 - 100	
8	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

155: D16 X Y FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3 HI			X
4 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
5 HI			Y
6 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535
7	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

**172: D CCT GM CRO XY FAN (PIXEL = 1; STROBE = OFF; FAN = ON)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5 HI			X
6 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
7 HI			Y
8 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535
9	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

173: D16 CCT GM CRO XY FAN (PIXEL = 1; STROBE = OFF; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
6 HI			X
7 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
8 HI			Y
9 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535
10	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

Pixel=1 Strobe=On Fan=On

156: RGBS FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
5	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined

157: RGBWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
5	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
6	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined

158: RGBAWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 255	0 - 100	Intensity Amber (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
6	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
7	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined

**159: DIM RGBS FAN (PIXEL = 1; STROBE = ON; FAN = ON)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
6	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

160: DIM RGBWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
6	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
7	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

161: DIM RGBAWS FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Intensity Red (0% → 100%)
3	0 - 255	0 - 100	Intensity Green (0% → 100%)
4	0 - 255	0 - 100	Intensity Blue (0% → 100%)
5	0 - 255	0 - 100	Intensity Amber (0% → 100%)
6	0 - 255	0 - 100	Intensity Emulated White (0% → 100%)
7	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
8	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined



DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

162: RGB CCT DIM IND S FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Intensity Red (0% → 100%)
2	0 - 255	0 - 100	Intensity Green (0% → 100%)
3	0 - 255	0 - 100	Intensity Blue (0% → 100%)
4	0 - 4 4 - 255	0 - 1.5 1.6 - 100	Color Temperature (CCT) No effect Display color temperature Formula: CCT = 2000 + 20*DMX-Value Example: 50 → 3000K 100 → 4000K 150 → 5000K <i>*CCT overwrites the RGB setting</i>
5	0..255	0 - 100	Dimmer (closed → open)
6	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors No effect Display Index Colors (full list at the end of this document) <i>*Index Colors overwrites both, RGB and CCT</i>
7	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
8	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

163: D CCT GM CRO RGB S FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32*DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5	0 - 255	0 - 100	Intensity Red (0% → 100%)
6	0 - 255	0 - 100	Intensity Green (0% → 100%)
7	0 - 255	0 - 100	Intensity Blue (0% → 100%)
8	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
9	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined



DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

164: D CCT GM HUE SAT S FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32*DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
4	0 - 255	0 - 100	Hue (0° → 360°)
5	0 - 255	0 - 100	Saturation (0% → 100%)
6	0 - 3 4 5 6 7 - 255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
7	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

165: D16 CCT GM C RGB S FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			
2 LO	0 - 65535	0 - 100	Dimmer closed → open
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32*DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
6	0 - 255	0 - 100	Intensity Red (0% → 100%)
7	0 - 255	0 - 100	Intensity Green (0% → 100%)
8	0 - 255	0 - 100	Intensity Blue (0% → 100%)
9	0 - 3 4 5 6 7 - 255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
10	0 - 255	0 - 100	Fan Control
	0 - 4	0 - 1.6	Fan Auto Speed
	5 - 35	2 - 13.7	Fan Slow Speed
	36 - 70	14 - 27.5	Fan Medium Speed
	71 - 100	28 - 39	Fan Fast Speed
	101 - 128	40 - 50	Fan Off
	129 - 255	51 - 100	Not Defined

**166: D16 CCT GM H SAT S FAN (PIXEL = 1; STROBE = ON; FAN = ON)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3	0 - 255	0 - 100	Color Temperature (CCT) Formular: CCT = 1750 + 32 * DMX-Value Example: 45 → 3190K 70 → 3990K 117 → 5494K
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: G/M = 100% * (DMX-Value/128 - 1)
5 HI			Hue
6 LO	0 - 65535	0 - 100	0° → 360°
7	0 - 255	0 - 100	Saturation (0% → 100%)
8	0 - 3 4 5 6 7 - 255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
9	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined

167: D16 X Y S FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI			Dimmer closed → open
2 LO	0 - 65535	0 - 100	
3 HI			X
4 LO	0 - 65535	0 - 100	Formular: x-Coordinate = 0.8 * DMX-Value / 65535
5 HI			Y
6 LO	0 - 65535	0 - 100	Formular: y-Coordinate = 0.8 * DMX-Value / 65535
7	0 - 3 4 5 6 7 - 255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
8	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined



DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

174: D CCT GM CRO XY S FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0 - 255	0 - 100	Dimmer (closed → open)
2	0 - 255	0 - 100	Color Temperature (CCT) Formular: $CCT = 1750 + 32 \cdot DMX\text{-Value}$ Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: $G/M = 100\% * (DMX\text{-Value}/128 - 1)$
4	0 - 255	0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5 HI	0 - 65535	0 - 100	X
6 LO			Formular: $x\text{-Coordinate} = 0.8 * DMX\text{-Value} / 65535$
7 HI	0 - 65535	0 - 100	Y
8 LO			Formular: $y\text{-Coordinate} = 0.8 * DMX\text{-Value} / 65535$
9	0 - 3 4 5 6 7 - 255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
10	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined

175: D16 CCT GM CRO XY S FAN (PIXEL = 1; STROBE = ON; FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1 HI	0 - 65535	0 - 100	Dimmer closed → open
2 LO			Color Temperature (CCT) Formular: $CCT = 1750 + 32 \cdot DMX\text{-Value}$ Example: 45 → 3190K 70 → 3990K 117 → 5494K
3	0 - 255	0 - 100	Green / Magenta Point No effect -96.1% → 100% Formular: $G/M = 100\% * (DMX\text{-Value}/128 - 1)$
4	0 - 4 5 - 255	0 - 1.5 2.0 - 100	Crossfade (0 full CCT, 255 full RGB, smooth fade)
5	0 - 255	0 - 100	X
6 HI	0 - 65535	0 - 100	Formular: $x\text{-Coordinate} = 0.8 * DMX\text{-Value} / 65535$
7 LO			Y
8 HI	0 - 65535	0 - 100	Formular: $y\text{-Coordinate} = 0.8 * DMX\text{-Value} / 65535$
9 LO			Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
10	0 - 3 4 5 6 7 - 255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined
11	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	



Effect Modes Fan=Off

15: EFFECT MODE FIX

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0.255	0 - 100	Dimmer of Pixel 1 (closed → open)
2	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2.0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
3	0 - 7 8 - 15 16 - 23 24 - 31 32 - 39 40 - 47 48 - 55 56 - 63 64 - 71 72 - 79 80 - 87 88 - 95 96 - 101 102 - 109 110 - 117 118 - 125 126 - 133 134 - 141 142 - 149 150 - 157	0 - 2.7 3.1 - 5.9 6.3 - 9.0 9.4 - 12.2 12.5 - 15.3 15.7 - 18.4 18.8 - 21.6 22.0 - 24.7 25.1 - 27.8 28.2 - 31.0 31.4 - 34.1 34.5 - 37.3 37.6 - 39.6 40.0 - 42.7 43.1 - 45.9 46.3 - 49.0 49.4 - 52.2 52.5 - 55.3 55.7 - 58.4 58.8 - 61.6	Program One Color Static Two Color Static Three Color Static Four Color Static One Color Fade Two Color Fade Three Color Fade Four Color Fade Simple Running Double Running Two Col Running Flag Running Double Flag Running Spiral 4 Color Spiral 2 Color Rainbow Fire Rotor Rotor Split 2 Rotor Split 4
4	0.255	0 - 100	Speed (slow → fast)
5	0.255	0 - 100	Crossfade (no fade → smooth fade)
6	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Direction Forward with Loop Forward one time and stop Reverse one time and stop Reverse with Loop
7	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Size <i>Defines the virtual size of the program in groups</i> <i>E.g. if SIZE is set to 2 groups only half of the program is shown on the unit.</i> 1 Group 2 Groups 3 Groups 4 Groups
8	0.255	0 - 100	Offset <i>If SIZE is set to >1 group, the units' pixels can be shifted within the virtually larger program.</i> <i>Increasing the OFFSET parameter scrolls the position of the unit within the virtual large program.</i>
9	0.255	0 - 100	Restart Program <i>If value is changed, the program starts again from the beginning (useful if DIRECTION is not set to loop).</i>
10	0.1 2.255	0 - 0.4 0.8 - 100	Index Colors 1 No effect Display Index Colors* (full list below)
11	0.1 2.255	0 - 0.4 0.8 - 100	Index Colors 2 No effect Display Index Colors* (full list below)
12	0.1 2.255	0 - 0.4 0.8 - 100	Index Colors 3 No effect Display Index Colors* (full list below)
13	0.1 2.255	0 - 0.4 0.8 - 100	Index Colors 4 No effect Display Index Colors* (full list below)

***Index Colors for 15: EFFECT MODE FIX**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
	0.1	0 - 0,4	No effect
	2	0,8	Rose Pink
	3	1,2	Lavender Tint
	4	1,6	Medium Bastard Amber
	7	2,7	Pale Yellow
	8	3,1	Dark Salmon
	9	3,5	Pale Amber Gold
	10	3,9	Medium Yellow
	13	5,1	Straw Tint
	15	5,9	Deep Straw
	17	6,7	Surprise Peach
	19	7,5	Fire
	20	7,8	Medium Amber
	21	8,2	Gold Amber
	22	8,6	Dark Amber
	24	9,4	Scarlet
	25	9,8	Sunset Red
	26	10,2	Bright Red
	27	10,6	Medium Red
	29	11,4	Plasa Red
	35	13,7	Light Pink
	36	14,1	Medium Pink
	46	18,0	Dark Magenta
	48	18,8	Rose Purple
	49	19,2	Medium Purple
	52	20,4	Light Lavender
	53	20,8	Paler Lavender
	58	22,7	Lavender
	61	23,9	Mist Blue
	63	24,7	Pale Blue
	68	26,7	Sky Blue
	71	27,8	Tokyo Blue
	75	29,4	Evening Blue
	79	31,0	Just Blue
	85	33,3	Deeper Blue
	88	34,5	Lime Green
	89	34,9	Moss Green
	90	35,3	Dark Yellow Green
	100	39,2	Spring Yellow
	101	39,6	Yellow
	102	40,0	Light Amber
	103	40,4	Straw
	104	40,8	Deep Amber
	105	41,2	Orange
	106	41,6	Primary Red
	107	42,0	Light Rose
	108	42,4	English Rose
	109	42,7	Light Salmon
	110	43,1	Middle Rose
	111	43,5	Dark Pink
	113	44,3	Magenta
	115	45,1	Peacock Blue
	116	45,5	Medium Blue-Green
	117	45,9	Steel Blue
	118	46,3	Light Blue
	119	46,7	Dark Blue
	120	47,1	Deep Blue
	121	47,5	LEE Green
	122	47,8	Fern Green
	124	48,6	Dark Green
	126	49,4	Mauve
	127	49,8	Smokey Pink
	128	50,2	Bright Pink
	129	50,6	Heavy Frost
	130	51,0	Clear
	131	51,4	Marine Blue



DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

132	51,8	Medium Blue
134	52,5	Golden Amber
135	52,9	Deep Golden Amber
136	53,3	Pale Lavender
137	53,7	Special Lavender
138	54,1	Pale Green
139	54,5	Primary Green
140	54,9	Summer Blue
141	55,3	Bright Blue
142	55,7	Pale Violet
143	56,1	Pale Navy Blue
144	56,5	No Color Blue
147	57,6	Apricot
148	58,0	Bright Rose
151	59,2	Gold Tint
152	59,6	Pale Gold
153	60,0	Pale Salmon
154	60,4	Pale Rose
156	61,2	Chocolate
157	61,6	Pink
158	62,0	Deep Orange
159	62,4	No Color Straw
161	63,1	Slate Blue
162	63,5	Bastard Amber
164	64,3	Flame Red
165	64,7	Daylight Blue
169	66,3	Lilac Tint
170	66,7	Deep Lavender
172	67,5	Lagoon Blue
174	68,2	Dark Steel Blue
176	69,0	Loving Amber
179	70,2	Chrome Orange
180	70,6	Dark Lavender
181	71,0	Congo Blue
182	71,4	Light Red
183	71,8	Moonlight Blue
184	72,2	Cosmetic Peach
186	72,9	Cosmetic Silver Rose
187	73,3	Cosmetic Rouge
188	73,7	Cosmetic Highlight
189	74,1	Cosmetic Silver Moss
191	74,9	Cosmetic Aqua Blue
192	75,3	Flesh Pink
194	76,1	Surprise Pink
195	76,5	Zenith Blue
196	76,9	True Blue
197	77,3	Alice Blue
198	77,6	Palace Blue
199	78,0	Regal Blue
200	78,4	Double CT Blue
201	78,8	Full CT Blue
202	79,2	1/2 CT Blue
203	79,6	1/4 CT Blue
204	80,0	Full CT Orange
205	80,4	1/2 CT Orange
206	80,8	1/4 CT Orange
207	81,2	Full CT Orange +
208	81,6	Full CT Orange +
209	82,0	0.3 Neutral Density
210	82,4	0.6 Neutral Density
211	82,7	0.9 Neutral Density
212	83,1	LCT Yellow
213	83,5	White Flame Green
216	84,7	White Diffusion
217	85,1	Blue Diffusion
218	85,5	1/8 CT Blue
219	85,9	LEE Fluorescent Green
220	86,3	White Frost
221	86,7	Blue Frost
223	87,5	1/8 CT Orange

**DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)**

224	87,8	Daylight Blue Frost
225	88,2	LEE N.D. Frost
226	88,6	LEE U.V.
228	89,4	Brushed Silk
229	89,8	1/4 Tough Spun
230	90,2	Super Correction
232	91,0	Super White Flame Green
236	92,5	H.M.I (To Tungsten)
237	92,9	C.I.D. (To Tungsten)
238	93,3	C.S.I. (To Tungsten)
239	93,7	Polarizer
241	94,5	LEE Fluorescent 5700 K
242	94,9	LEE Fluorescent 4300 K
243	95,3	LEE Fluorescent 3600 K
244	95,7	LEE Plus Green
245	96,1	1/2 Plus Green
246	96,5	1/4 Plus Green
247	96,9	LEE Minus Green
248	97,3	1/2 Minus Green
249	97,6	1/4 Minus Green
250	98,0	1/2 White Diffusion
251	98,4	1/4 White Diffusion
252	98,8	1/8 White Diffusion
253	99,2	Hampshire Frost
254	99,6	New Hampshire Frost
255	100,0	Hollywood Frost



16: EFFECT MODE RGB

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0.255	0 - 100	Dimmer of Pixel 1 (closed → open)
2	0 - 3 4 5 6 7 - 255	0 - 1.2 1.6 2.0 2.4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
3	0 - 7 8 - 15 16 - 23 24 - 31 32 - 39 40 - 47 48 - 55 56 - 63 64 - 71 72 - 79 80 - 87 88 - 95 96 - 101 102 - 109 110 - 117 118 - 125 126 - 133 134 - 141 142 - 149 150 - 157	0 - 2.7 3.1 - 5.9 6.3 - 9.0 9.4 - 12.2 12.5 - 15.3 15.7 - 18.4 18.8 - 21.6 22.0 - 24.7 25.1 - 27.8 28.2 - 31.0 31.4 - 34.1 34.5 - 37.3 37.6 - 39.6 40.0 - 42.7 43.1 - 45.9 46.3 - 49.0 49.4 - 52.2 52.5 - 55.3 55.7 - 58.4 58.8 - 61.6	Program One Color Static Two Color Static Three Color Static Four Color Static One Color Fade Two Color Fade Three Color Fade Four Color Fade Simple Running Double Running Two Col Running Flag Running Double Flag Running Spiral 4 Color Spiral 2 Color Rainbow Fire Rotor Rotor Split 2 Rotor Split 4
4	0.255	0 - 100	Speed (slow → fast)
5	0.255	0 - 100	Crossfade (no fade → smooth fade)
6	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Direction Forward with Loop Forward one time and stop Reverse one time and stop Reverse with Loop
7	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Size <i>Defines the virtual size of the program in groups</i> <i>E.g. if SIZE is set to 2 groups only half of the program is shown on the unit.</i> 1 Group 2 Groups 3 Groups 4 Groups
8	0.255	0 - 100	Offset <i>If SIZE is set to >1 group, the units' pixels can be shifted within the virtually larger program.</i> <i>Increasing the OFFSET parameter scrolls the position of the unit within the virtual large program.</i>
9	0.255	0 - 100	Restart Program <i>If value is changed, the program starts again from the beginning (useful if DIRECTION is not set to loop).</i>
10	0 - 255	0 - 100	Intensity Red of Color 1 (0% → 100%)
11	0 - 255	0 - 100	Intensity Green of Color 1 (0% → 100%)
12	0 - 255	0 - 100	Intensity Blue of Color 1 (0% → 100%)
13	0 - 255	0 - 100	Intensity Red of Color 2 (0% → 100%)
14	0 - 255	0 - 100	Intensity Green of Color 2 (0% → 100%)
15	0 - 255	0 - 100	Intensity Blue of Color 2 (0% → 100%)
16	0 - 255	0 - 100	Intensity Red of Color 3 (0% → 100%)
17	0 - 255	0 - 100	Intensity Green of Color 3 (0% → 100%)
18	0 - 255	0 - 100	Intensity Blue of Color 3 (0% → 100%)
19	0 - 255	0 - 100	Intensity Red of Color 4 (0% → 100%)
20	0 - 255	0 - 100	Intensity Green of Color 4 (0% → 100%)
21	0 - 255	0 - 100	Intensity Blue of Color 4 (0% → 100%)

Effect Modes Fan=On

176: EFFECT MODE FIX FAN (FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0..255	0 - 100	Dimmer of Pixel 1 (closed → open)
2	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2,0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
3	0 - 7 8 - 15 16 - 23 24 - 31 32 - 39 40 - 47 48 - 55 56 - 63 64 - 71 72 - 79 80 - 87 88 - 95 96 - 101 102 - 109 110 - 117 118 - 125 126 - 133 134 - 141 142 - 149 150 - 157	0 - 2.7 3.1 - 5.9 6.3 - 9.0 9.4 - 12.2 12.5 - 15.3 15.7 - 18.4 18.8 - 21.6 22.0 - 24.7 25.1 - 27.8 28.2 - 31.0 31.4 - 34.1 34.5 - 37.3 37.6 - 39.6 40.0 - 42.7 43.1 - 45.9 46.3 - 49.0 49.4 - 52.2 52.5 - 55.3 55.7 - 58.4 58.8 - 61.6	Program One Color Static Two Color Static Three Color Static Four Color Static One Color Fade Two Color Fade Three Color Fade Four Color Fade Simple Running Double Running Two Col Running Flag Running Double Flag Running Spiral 4 Color Spiral 2 Color Rainbow Fire Rotor Rotor Split 2 Rotor Split 4
4	0..255	0 - 100	Speed (slow → fast)
5	0..255	0 - 100	Crossfade (no fade → smooth fade)
6	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Direction Forward with Loop Forward one time and stop Reverse one time and stop Reverse with Loop
7	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Size <i>Defines the virtual size of the program in groups</i> <i>E.g. if SIZE is set to 2 groups only half of the program is shown on the unit.</i> 1 Group 2 Groups 3 Groups 4 Groups
8	0..255	0 - 100	Offset <i>If SIZE is set to >1 group, the units' pixels can be shifted within the virtually larger program.</i> <i>Increasing the OFFSET parameter scrolls the position of the unit within the virtual large program.</i>
9	0..255	0 - 100	Restart Program <i>If value is changed, the program starts again from the beginning (useful if DIRECTION is not set to loop).</i>
10	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors 1 No effect Display Index Colors* (full list below)
11	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors 2 No effect Display Index Colors* (full list below)
12	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors 3 No effect Display Index Colors* (full list below)
13	0..1 2..255	0 - 0.4 0.8 - 100	Index Colors 4 No effect Display Index Colors* (full list below)
14	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined

***Index Colors for 176: EFFECT MODE FIX FAN (FAN = ON)**

CHANNEL	VALUE	PERCENTAGE	FUNCTION
	0.1	0 - 0,4	No effect
	2	0,8	Rose Pink
	3	1,2	Lavender Tint
	4	1,6	Medium Bastard Amber
	7	2,7	Pale Yellow
	8	3,1	Dark Salmon
	9	3,5	Pale Amber Gold
	10	3,9	Medium Yellow
	13	5,1	Straw Tint
	15	5,9	Deep Straw
	17	6,7	Surprise Peach
	19	7,5	Fire
	20	7,8	Medium Amber
	21	8,2	Gold Amber
	22	8,6	Dark Amber
	24	9,4	Scarlet
	25	9,8	Sunset Red
	26	10,2	Bright Red
	27	10,6	Medium Red
	29	11,4	Plasa Red
	35	13,7	Light Pink
	36	14,1	Medium Pink
	46	18,0	Dark Magenta
	48	18,8	Rose Purple
	49	19,2	Medium Purple
	52	20,4	Light Lavender
	53	20,8	Paler Lavender
	58	22,7	Lavender
	61	23,9	Mist Blue
	63	24,7	Pale Blue
	68	26,7	Sky Blue
	71	27,8	Tokyo Blue
	75	29,4	Evening Blue
	79	31,0	Just Blue
	85	33,3	Deeper Blue
	88	34,5	Lime Green
	89	34,9	Moss Green
	90	35,3	Dark Yellow Green
	100	39,2	Spring Yellow
	101	39,6	Yellow
	102	40,0	Light Amber
	103	40,4	Straw
	104	40,8	Deep Amber
	105	41,2	Orange
	106	41,6	Primary Red
	107	42,0	Light Rose
	108	42,4	English Rose
	109	42,7	Light Salmon
	110	43,1	Middle Rose
	111	43,5	Dark Pink
	113	44,3	Magenta
	115	45,1	Peacock Blue
	116	45,5	Medium Blue-Green
	117	45,9	Steel Blue
	118	46,3	Light Blue
	119	46,7	Dark Blue
	120	47,1	Deep Blue
	121	47,5	LEE Green
	122	47,8	Fern Green
	124	48,6	Dark Green
	126	49,4	Mauve
	127	49,8	Smokey Pink
	128	50,2	Bright Pink
	129	50,6	Heavy Frost
	130	51,0	Clear
	131	51,4	Marine Blue



DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

132	51,8	Medium Blue
134	52,5	Golden Amber
135	52,9	Deep Golden Amber
136	53,3	Pale Lavender
137	53,7	Special Lavender
138	54,1	Pale Green
139	54,5	Primary Green
140	54,9	Summer Blue
141	55,3	Bright Blue
142	55,7	Pale Violet
143	56,1	Pale Navy Blue
144	56,5	No Color Blue
147	57,6	Apricot
148	58,0	Bright Rose
151	59,2	Gold Tint
152	59,6	Pale Gold
153	60,0	Pale Salmon
154	60,4	Pale Rose
156	61,2	Chocolate
157	61,6	Pink
158	62,0	Deep Orange
159	62,4	No Color Straw
161	63,1	Slate Blue
162	63,5	Bastard Amber
164	64,3	Flame Red
165	64,7	Daylight Blue
169	66,3	Lilac Tint
170	66,7	Deep Lavender
172	67,5	Lagoon Blue
174	68,2	Dark Steel Blue
176	69,0	Loving Amber
179	70,2	Chrome Orange
180	70,6	Dark Lavender
181	71,0	Congo Blue
182	71,4	Light Red
183	71,8	Moonlight Blue
184	72,2	Cosmetic Peach
186	72,9	Cosmetic Silver Rose
187	73,3	Cosmetic Rouge
188	73,7	Cosmetic Highlight
189	74,1	Cosmetic Silver Moss
191	74,9	Cosmetic Aqua Blue
192	75,3	Flesh Pink
194	76,1	Surprise Pink
195	76,5	Zenith Blue
196	76,9	True Blue
197	77,3	Alice Blue
198	77,6	Palace Blue
199	78,0	Regal Blue
200	78,4	Double CT Blue
201	78,8	Full CT Blue
202	79,2	1/2 CT Blue
203	79,6	1/4 CT Blue
204	80,0	Full CT Orange
205	80,4	1/2 CT Orange
206	80,8	1/4 CT Orange
207	81,2	Full CT Orange +
208	81,6	Full CT Orange +
209	82,0	0.3 Neutral Density
210	82,4	0.6 Neutral Density
211	82,7	0.9 Neutral Density
212	83,1	LCT Yellow
213	83,5	White Flame Green
216	84,7	White Diffusion
217	85,1	Blue Diffusion
218	85,5	1/8 CT Blue
219	85,9	LEE Fluorescent Green
220	86,3	White Frost
221	86,7	Blue Frost
223	87,5	1/8 CT Orange

**DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)**

224	87,8	Daylight Blue Frost
225	88,2	LEE N.D. Frost
226	88,6	LEE U.V.
228	89,4	Brushed Silk
229	89,8	1/4 Tough Spun
230	90,2	Super Correction
232	91,0	Super White Flame Green
236	92,5	H.M.I (To Tungsten)
237	92,9	C.I.D. (To Tungsten)
238	93,3	C.S.I. (To Tungsten)
239	93,7	Polarizer
241	94,5	LEE Fluorescent 5700 K
242	94,9	LEE Fluorescent 4300 K
243	95,3	LEE Fluorescent 3600 K
244	95,7	LEE Plus Green
245	96,1	1/2 Plus Green
246	96,5	1/4 Plus Green
247	96,9	LEE Minus Green
248	97,3	1/2 Minus Green
249	97,6	1/4 Minus Green
250	98,0	1/2 White Diffusion
251	98,4	1/4 White Diffusion
252	98,8	1/8 White Diffusion
253	99,2	Hampshire Frost
254	99,6	New Hampshire Frost
255	100,0	Hollywood Frost

177: EFFECT MODE RGB FAN (FAN = ON)

CHANNEL	VALUE	PERCENTAGE	FUNCTION
1	0..255	0 - 100	Dimmer of Pixel 1 (closed → open)
2	0 - 3 4 5 6 7 - 255	0 - 1.2 1,6 2,0 2,4 2.7 - 100	Strobe Off Random Fast Random Medium Random Slow Variable Strobe (0.4Hz → 25Hz)
3	0 - 7 8 - 15 16 - 23 24 - 31 32 - 39 40 - 47 48 - 55 56 - 63 64 - 71 72 - 79 80 - 87 88 - 95 96 - 101 102 - 109 110 - 117 118 - 125 126 - 133 134 - 141 142 - 149 150 - 157	0 - 2.7 3.1 - 5.9 6.3 - 9.0 9.4 - 12.2 12.5 - 15.3 15.7 - 18.4 18.8 - 21.6 22.0 - 24.7 25.1 - 27.8 28.2 - 31.0 31.4 - 34.1 34.5 - 37.3 37.6 - 39.6 40.0 - 42.7 43.1 - 45.9 46.3 - 49.0 49.4 - 52.2 52.5 - 55.3 55.7 - 58.4 58.8 - 61.6	Program One Color Static Two Color Static Three Color Static Four Color Static One Color Fade Two Color Fade Three Color Fade Four Color Fade Simple Running Double Running Two Col Running Flag Running Double Flag Running Spiral 4 Color Spiral 2 Color Rainbow Fire Rotor Rotor Split 2 Rotor Split 4
4	0..255	0 - 100	Speed (slow → fast)
5	0..255	0 - 100	Crossfade (no fade → smooth fade)
6	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Direction Forward with Loop Forward one time and stop Reverse one time and stop Reverse with Loop
7	0 - 63 64 - 127 128 - 190 191 - 255	0 - 24.7 25.1 - 49.8 50.2 - 74.5 74.9 - 100	Size <i>Defines the virtual size of the program in groups</i> <i>E.g. if SIZE is set to 2 groups only half of the program is shown on the unit.</i> 1 Group 2 Groups 3 Groups 4 Groups
8	0..255	0 - 100	Offset <i>If SIZE is set to >1 group, the units' pixels can be shifted within the virtually larger program.</i> <i>Increasing the OFFSET parameter scrolls the position of the unit within the virtual large program.</i>
9	0..255	0 - 100	Restart Program <i>If value is changed, the program starts again from the beginning (useful if DIRECTION is not set to loop).</i>
10	0 - 255	0 - 100	Intensity Red of Color 1 (0% → 100%)
11	0 - 255	0 - 100	Intensity Green of Color 1 (0% → 100%)
12	0 - 255	0 - 100	Intensity Blue of Color 1 (0% → 100%)
13	0 - 255	0 - 100	Intensity Red of Color 2 (0% → 100%)
14	0 - 255	0 - 100	Intensity Green of Color 2 (0% → 100%)
15	0 - 255	0 - 100	Intensity Blue of Color 2 (0% → 100%)
16	0 - 255	0 - 100	Intensity Red of Color 3 (0% → 100%)
17	0 - 255	0 - 100	Intensity Green of Color 3 (0% → 100%)
18	0 - 255	0 - 100	Intensity Blue of Color 3 (0% → 100%)
19	0 - 255	0 - 100	Intensity Red of Color 4 (0% → 100%)
20	0 - 255	0 - 100	Intensity Green of Color 4 (0% → 100%)
21	0 - 255	0 - 100	Intensity Blue of Color 4 (0% → 100%)
22	0 - 255 0 - 4 5 - 35 36 - 70 71 - 100 101 - 128 129 - 255	0 - 100 0 - 1.6 2 - 13.7 14 - 27.5 28 - 39 40 - 50 51 - 100	Fan Control Fan Auto Speed Fan Slow Speed Fan Medium Speed Fan Fast Speed Fan Off Not Defined

Index Colors

CHANNEL	VALUE	PERCENTAGE	FUNCTION
	0..3	0 - 1,2	No effect
	4	1,6	Medium Bastard Amber
	7	2,7	Pale Yellow
	8	3,1	Dark Salmon
	9	3,5	Pale Amber Gold
	10	3,9	Medium Yellow
	13	5,1	Straw Tint
	15	5,9	Deep Straw
	17	6,7	Surprise Peach
	19	7,5	Fire
	20	7,8	Medium Amber
	21	8,2	Gold Amber
	22	8,6	Dark Amber
	24	9,4	Scarlet
	25	9,8	Sunset Red
	26	10,2	Bright Red
	27	10,6	Medium Red
	29	11,4	Plasa Red
	35	13,7	Light Pink
	36	14,1	Medium Pink
	46	18,0	Dark Magenta
	48	18,8	Rose Purple
	49	19,2	Medium Purple
	52	20,4	Light Lavender
	53	20,8	Paler Lavender
	58	22,7	Lavender
	61	23,9	Mist Blue
	63	24,7	Pale Blue
	68	26,7	Sky Blue
	71	27,8	Tokyo Blue
	75	29,4	Evening Blue
	79	31,0	Just Blue
	85	33,3	Deeper Blue
	88	34,5	Lime Green
	89	34,9	Moss Green
	90	35,3	Dark Yellow Green
	100	39,2	Spring Yellow
	101	39,6	Yellow
	102	40,0	Light Amber
	103	40,4	Straw
	104	40,8	Deep Amber
	105	41,2	Orange
	106	41,6	Primary Red
	107	42,0	Light Rose
	108	42,4	English Rose
	109	42,7	Light Salmon
	110	43,1	Middle Rose
	111	43,5	Dark Pink
	113	44,3	Magenta
	115	45,1	Peacock Blue
	116	45,5	Medium Blue-Green
	117	45,9	Steel Blue
	118	46,3	Light Blue
	119	46,7	Dark Blue
	120	47,1	Deep Blue
	121	47,5	LEE Green
	122	47,8	Fern Green
	124	48,6	Dark Green
	126	49,4	Mauve
	127	49,8	Smokey Pink
	128	50,2	Bright Pink
	129	50,6	Heavy Frost
	130	51,0	Clear
	131	51,4	Marine Blue
	132	51,8	Medium Blue
	134	52,5	Golden Amber

DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)

	135	52,9	Deep Golden Amber
	136	53,3	Pale Lavender
	137	53,7	Special Lavender
	138	54,1	Pale Green
	139	54,5	Primary Green
	140	54,9	Summer Blue
	141	55,3	Bright Blue
	142	55,7	Pale Violet
	143	56,1	Pale Navy Blue
	144	56,5	No Color Blue
	147	57,6	Apricot
	148	58,0	Bright Rose
	151	59,2	Gold Tint
	152	59,6	Pale Gold
	153	60,0	Pale Salmon
	154	60,4	Pale Rose
	156	61,2	Chocolate
	157	61,6	Pink
	158	62,0	Deep Orange
	159	62,4	No Color Straw
	161	63,1	Slate Blue
	162	63,5	Bastard Amber
	164	64,3	Flame Red
	165	64,7	Daylight Blue
	169	66,3	Lilac Tint
	170	66,7	Deep Lavender
	172	67,5	Lagoon Blue
	174	68,2	Dark Steel Blue
	176	69,0	Loving Amber
	179	70,2	Chrome Orange
	180	70,6	Dark Lavender
	181	71,0	Congo Blue
	182	71,4	Light Red
	183	71,8	Moonlight Blue
	184	72,2	Cosmetic Peach
	186	72,9	Cosmetic Silver Rose
	187	73,3	Cosmetic Rouge
	188	73,7	Cosmetic Highlight
	189	74,1	Cosmetic Silver Moss
	191	74,9	Cosmetic Aqua Blue
	192	75,3	Flesh Pink
	194	76,1	Surprise Pink
	195	76,5	Zenith Blue
	196	76,9	True Blue
	197	77,3	Alice Blue
	198	77,6	Palace Blue
	199	78,0	Regal Blue
	200	78,4	Double CT Blue
	201	78,8	Full CT Blue
	202	79,2	1/2 CT Blue
	203	79,6	1/4 CT Blue
	204	80,0	Full CT Orange
	205	80,4	1/2 CT Orange
	206	80,8	1/4 CT Orange
	207	81,2	Full CT Orange +
	208	81,6	Full CT Orange +
	209	82,0	0.3 Neutral Density
	210	82,4	0.6 Neutral Density
	211	82,7	0.9 Neutral Density
	212	83,1	LCT Yellow
	213	83,5	White Flame Green
	216	84,7	White Diffusion
	217	85,1	Blue Diffusion
	218	85,5	1/8 CT Blue
	219	85,9	LEE Fluorescent Green
	220	86,3	White Frost
	221	86,7	Blue Frost
	223	87,5	1/8 CT Orange
	224	87,8	Daylight Blue Frost
	225	88,2	LEE N.D. Frost

**DMX Profiles for PlutoFresnel (AF80) and LeoFresnel (AF250)**

226	88,6	LEE U.V.
228	89,4	Brushed Silk
229	89,8	1/4 Tough Spun
230	90,2	Super Correction
232	91,0	Super White Flame Green
236	92,5	H.M.I (To Tungsten)
237	92,9	C.I.D. (To Tungsten)
238	93,3	C.S.I. (To Tungsten)
239	93,7	Polarizer
241	94,5	LEE Fluorescent 5700 K
242	94,9	LEE Fluorescent 4300 K
243	95,3	LEE Fluorescent 3600 K
244	95,7	LEE Plus Green
245	96,1	1/2 Plus Green
246	96,5	1/4 Plus Green
247	96,9	LEE Minus Green
248	97,3	1/2 Minus Green
249	97,6	1/4 Minus Green
250	98,0	1/2 White Diffusion
251	98,4	1/4 White Diffusion
252	98,8	1/8 White Diffusion
253	99,2	Hampshire Frost
254	99,6	New Hampshire Frost
255	100,0	Hollywood Frost