

LightDrop



Optical

Colours

RGBW

Total LED power

Luminous Flux

Emittance (@2m)

Strobe

0-25Hz

Beam Angle

13

Pixels

Electrical

Battery

Battery Lifetime

70% after 300 cycles

Battery Runtime

Charging time (nominal)

7 Hours

Input Voltage (charger)

90-264V 47-63Hz

Input voltage (light)

5V 2.5A

Control

Wireless Modules

865-870MHz 902-928MHz 2.4GHz

Range

Wireless DMX

CRMX & others, excluding W-DMX G5, City Theatrical

Construction

Housing

IP Rating

Relative humidity

Operating Temperature

0-40 °C 32-104 °F

Weight

1.4Lbs

Dimensions (with bracket)

120 x 59 x 114 (mm) $7.4 \times 2.3 \times 4.4$ (inches)

Accessories



Charger

AX3-CHR (Included)



Hooks (3)

AX3-EBLT (Included)



Rubber Feet (4)

AX3-FEET (Included)



AX3-STA (Included)



30° diffuser

AX3-DDSK30 (Included)



120° diffuser

AX3-DDSK-120(Included)



Wallwash diffuser

AX3-WWDSK



Diffuser dome

AX3-DDM



Charging case

AX3-CHRCSE

