



AX7 SpotLite



Optical

Colours
RGBW
Total LED power
60W
Luminous Flux
1675Lm
Emittance (@2m)
6250Lx
Strobe
0-25Hz
Beam Angle
13°
Pixels
1

Construction



Housing
Aluminium
IP Rating
IP65
Relative humidity
0-100%
Operating Temperature
0-40 °C
32-104 °F
Weight
6.1kg
13.4Lbs
Dimensions
279 x 296 x 253 (mm)
10.9 x 11.6 x 9.9 (inches)

Accessories

-  Powercon True1 cord
AX10-CHR (Included)
-  32° Flood diffusor
AX10-DDSK (Included)
-  13°x 46° Wallwash diffusor
AX10-WWDSK (Included)
-  13°x 46° Rotatable diffusor
AX10-ROTAD
-  Charging case
AX10-CHRCSE
-  Super bolt
AX10-BLT

Electrical

Battery
LG Chem Lithium-ion
Battery Lifetime
70% after 300 cycles
Charging time (nominal)
7 Hours
Input Voltage
90-264V 47-63Hz
Input Current
1.8A/115VAC ~ 1.0A/230VAC
Inrush Current
Cold start 60A/230VAC



Control

Wireless Modules
865-870MHz
902-928MHz
2.4GHz
Range
300m | 330 Yards
DMX
Supports CRMX and W-DMX

