



Datasheet

Charging Case & Set for PixelBrick

Date: 18-Jul-2025 Version: 2.0



Sturdy charging and transportation case with 2 wheels and 3 handles to carry 8 PixelBricks. The included power supply can charge 8 tubes from one AC outlet. Also available as Set with PixelBricks, BrickConnects and Filters.

Empty case



Full case



SPECIFICATIONS

	Charging Case	PixelBrick Set
Order Code	PB15-CHRCSE-EU / -US / -UK / -CH / -AU	PB15-SET-EU / -US / -UK / -CH / -AU
AC Input	100-240 VAC, 50 / 60 Hertz, 1.8 A / 115 VAC, 1 A / 230 VAC, 200 W	
AC Connector	PowerCON TRUE1 IN / OUT	
DC Output	2 x 24 VDC / 2 x 86 W	
DC Connector	2 x DC Barrel (5.5 mm / 2.1 mm)	
Weight (empty)	6.8 kg / 15 lbs	
Weight (full)	16.3 kg / 36 lbs	
Dimensions (L x W x D)	541.5 mm x 400 mm x 205.5 mm / 21.3" x 17.44" x 8.1"	

All specifications provided are typical values and maybe subject to change without prior notice.

CAN HOLD

Charging Case	PixelBrick Set
1x PowerBox (PWB-2-86)	1x PowerBox (PWB-2-86)
1x PowerCon True1 cable	1x PowerCon True1 cable
-	8x PixelBrick (PB15)
-	8x BrickConnect (PB15-BCN)
-	8x FloodFilter (PB15-FF)
-	8x BeamSoftener (PB15-BSO)

DRAWINGS

